

Open the door to better environmental control for your business.

The advanced design of the Rollflex Door delivers a secure fit that is ideal for protecting sensitive product and work environment.



rollflex

Rapid Auto Roll Door



BENEFITS AND SAFETY FEATURES

The Rollflex Door comes with a number of standard benefits and safety features. Among these are:

- Size up to 6000H x 6000W, with Strong Aluminium extruded door structure, clear matt Anodized for corrosion protection.
- Inline safety beam reverses door immediately if beam is disturbed.
- Pneumatic safety strip is available as option for auto reverse of Bottom bar
- Opening speed of 1.5 meters / second with single phase, 230 volts AC (10 AMP) power input and 0.9 meter / second with 3 phase 415 volts AC (10 AMP) power input.
- Exclusive dedicated controller designed to accept all modern activation control and safety features.
- Door panel manufactured from Polyester reinforced fire retardant PVC coated with UV absorbers and including a clear PVC safety vision panel. Variety of panel design options available. PVC panels are interchangeable and individual panel can be replaced if required.
- Intermediate Aluminium ribs for added support to the door panels.
- Vertical brushes for optimum sealing of the panel. Bottom Rubber seals gap on floor to meet floor irregularities.
- All components, including the panels, are available as spare ex-stocks.

spanker
INTERNATIONAL

We have a solution to suit every doorway problem!


rolflex

Rapid Auto Roll Door

DOOR CONTROL OPTIONS:


The Rollflex Door have a variety of door control options to deliver maximum performance that best suits your requirements. These will be influenced by the door's application which includes the speed, mix and frequency of your traffic flow.

Our representative is well trained to evaluate your specific needs and can recommend the best option for you. These choices may include:




Radar Motion Detectors

The radar beam detects movement and activates the door. IR Sensor & Microwave Sensor works on same principle.



Induction Floor Loops

The loop in the floor reacts by magnetic attraction to open the door. Loops can operate for one way or two way traffic.



Remote Control

A radio transmitter carried by the driver opens the door.






Photo Cells

By breaking the beam, the door opens, then closes by time delay.



Push Buttons



Pull Switch

Solving your door problems

Doors are manufactured using our proven modular componentry systems and advanced production techniques. We can design, supply and install all of your door requirements quickly and efficiently, to solve your doorway problems, simply and economically.

Information contained herein is to the best of our knowledge and belief, accurate and reliable. Use of any of the materials featured in this catalog is the sole responsibility of the end-user of our product.

Spanker International has a continuous program of Product Development and reserves the right to change specifications at any time without notice.

Your local distributor:

The energy efficient
Rollflex Doors
Now easily affordable...



SERVICE AND SUPPORT

Spanker International offers a wide range of door systems to suit a variety of applications in business and industry. Our qualified technical staff will help you consider alternative models from one of the broadest range available.

spanker
INTERNATIONAL

27, Gopi Estate, Bh. Spice World, Changodar,
Ahmedabad - 382213 INDIA. Tele : +91-2717-251581/325998
Fax : +91-2717-251580 Email : sales@spanker.in

www.spanker.in