

# Strip Curtain Doors

**For Quotation Please complete this Quick Quotation Form and Fax to +91-2717-251580 or call: +91-2717-251581/325998**

ACTUAL DOOR OPENING DIMENSIONS : Height \_\_\_\_\_ (mm) Width \_\_\_\_\_ (mm)

DOOR LOCATION :  Shipping  Receiving Door  Cooler / Freezer  Refrigerated Truck

Others : \_\_\_\_\_

PRESENT DOOR TYPE :  Hinged  Swinging  Sliding  Roll-up

INTENDED APPLICATION :  Thermal Barrier  Fly/bird Control  Noise Control

Welding Screen  Dust Barrier  Enclosure

TRAFFIC THRU DOORWAY:  Personnel  Forklift  Trucks  Other

## ADDITIONAL INFORMATION -


Does doorway open directly to outside of the building ?  Yes  No

Draft conditions through doorway?  None  Slight  Heavy


Approximate clearance between highest load (or forklift) and door header : \_\_\_\_\_

## Please Indicate Any Specific Requirements :

### Select Fixing Type



FACE FIXING



HEAD FIXING

### Select PVC Type

- Plane Normal Temperature (4° C to 65° C)
- Plane Freezer Temperature (-40° C to +4° C)
- Double Ribbed Normal Temperature (4° C to 65° C)
- Anti Insect Amber (4° C to 65° C)
- Anti Static (4° C to 65° C)
- Plane Marker Red
- Plane Dark Green Welding Screen

### State Any Obstruction To Door Fixing (window, joist, pipe, etc.)

(Please illustrate on diagram above)

Your Name : \_\_\_\_\_

Company : \_\_\_\_\_

Address : \_\_\_\_\_

Phone : \_\_\_\_\_

Fax : \_\_\_\_\_

Email : \_\_\_\_\_

### Optional Extras :

- Stainless Steel Head Rail  Powder Coated Head Rail
- Bottom Reinforcement  Sliding Arrangement
- Safety Marker Strips

**spanker**  
INTERNATIONAL

27, Gopi Estate, Bh. Spice World, Changodar,  
Ahmedabad - 382213 INDIA. Tele : +91-2717-251581/325998  
Fax : +91-2717-251580 Email : sales@spanker.in

**www.spanker.in**